

TFT LCD MODULE

5" WVGA TFT LCD

350 nit 800 × 480 display with Parallel RGB (TTL) interface.

DCL P/N

100432-01



TAA COMPLIANT



5"

DIAGONAL

350

NITS

800×480

WVGA

-20~70°C

OPERATING

KEY FEATURES

- 130° / 110° viewing angle
- 350 nit LED backlight
- 600:1 contrast ratio
- -20 °C to +70 °C operating range
- Parallel RGB (TTL) interface
- Touch panel, cover glass and optical bonding available
- Custom FPC, cable assembly and driver-board options

SPECIFICATIONS

Size	5" (WVGA)
Resolution	800 × 480
Display Technology	TFT LCD
Brightness	350 cd/m ²
Contrast Ratio	600:1
Viewing Angle (H/V)	130° / 110°
Interface	Parallel RGB (TTL)
Connector	50-pin
Operating Temp.	-20 ~ +70 °C
DCL Part Number	100432-01

APPLICATIONS Handheld devices · Appliances · Instrumentation

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com