TFT LCD MODULE

5" WVGA High-Brightness IPS TFT LCD

1000 nit 800 × 480 display with Parallel RGB (TTL) interface — sunlight-readable, wide-temperature, Hi-Tni design.

DCL P/N 100435-01 · TAA COMPLIANT

5"	1000	800×480	-30~80°C
DIAGONAL	NITS	WVGA	OPERATING

KEY FEATURES

- IPS technology — 160° / 160° viewing, consistent color off-axis
- 1000 nit LED backlight — sunlight-readable
- 1000:1 contrast ratio
- -30 °C to +80 °C operating range with Hi-Tni liquid crystal
- Parallel RGB (TTL) interface
- Touch panel, cover glass and optical bonding available
- Custom FPC, cable assembly and driver-board options

SPECIFICATIONS

Size	**5" (WVGA)**
Resolution	**800 × 480**
Display Technology	**TFT LCD, IPS, Hi-Tni LC**
Brightness	**1000 cd/m²**
Contrast Ratio	**1000:1**
Viewing Angle (H/V)	**160° / 160°**
Interface	**Parallel RGB (TTL)**
Operating Temp.	**-30 ~ +80 °C**
DCL Part Number	**100435-01**

APPLICATIONS Handheld devices · Appliances · Instrumentation · Outdoor equipment · Marine

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.