

TFT LCD MODULE

7" WVGA High-Brightness TFT LCD


1000 nit 800 × 480 display with Parallel RGB (TTL) interface — sunlight-readable design.

DCL P/N

100469-01



TAA COMPLIANT



7"

DIAGONAL

1000

NITS

800×480

WVGA

-20~70°C

OPERATING

KEY FEATURES

- 130° / 110° viewing angle
- 1000 nit LED backlight — sunlight-readable
- 500:1 contrast ratio
- -20 °C to +70 °C operating range
- Parallel RGB (TTL) interface
- Square-pixel panel for true-proportion graphics
- Touch panel, cover glass and optical bonding available
- Custom FPC, cable assembly and driver-board options

SPECIFICATIONS

Size	7" (WVGA)
Resolution	800 × 480
Display Technology	TFT LCD
Brightness	1000 cd/m ²
Contrast Ratio	500:1
Viewing Angle (H/V)	130° / 110°
Interface	Parallel RGB (TTL)
Connector	60-pin
Operating Temp.	-20 ~ +70 °C
DCL Part Number	100469-01

APPLICATIONS Industrial HMI · Medical devices · EV charging · Outdoor equipment · Marine

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com