TFT LCD MODULE

19" SXGA High-Brightness TFT LCD

1000 nit 1280 × 1024 display with LVDS interface — sunlight-readable design.

DCL P/N **100843-01** TAA COMPLIANT

19"	1000	1280×1024	-15~70°C
DIAGONAL	NITS	SXGA	OPERATING

KEY FEATURES

- 178° / 178° viewing angle
- 1000 nit LED backlight — sunlight-readable
- 2000:1 contrast ratio
- -15 °C to +70 °C operating range
- LVDS interface
- Touch panel, cover glass and optical bonding available
- Custom FPC, cable assembly and driver-board options

SPECIFICATIONS

Size	**19" (SXGA)**
Resolution	**1280 × 1024**
Display Technology	**TFT LCD**
Brightness	**1000 cd/m²**
Contrast Ratio	**2000:1**
Viewing Angle (H/V)	**178° / 178°**
Interface	**LVDS**
Operating Temp.	**-15 ~ +70 °C**
DCL Part Number	**100843-01**

APPLICATIONS Kiosks · Industrial HMI · Medical displays · Outdoor equipment · Marine

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.