

LCD TOUCH DISPLAY MODULE

19" SXGA Resistive Touch Display Module

Integrated LCD + resistive touch module, 350–1500 nit brightness options, ready to drop into your enclosure.

DCL P/N

312364-01



TAA COMPLIANT



19"

DIAGONAL

1500

NITS MAX

1280×1024

SXGA

RTP

TOUCH

KEY FEATURES

- 4/5-wire resistive touch — works with gloves and stylus
- Brightness options from 350 to 1500 nits for indoor to sunlight-readable use
- 1280 × 1024 SXGA resolution
- LVDS video interface
- USB touch interface, I2C / RS232 optional
- Factory-integrated LCD, touch sensor and cover glass — one part number
- Optical bonding, AG / AR / AF glass and custom cover-lens printing available

SPECIFICATIONS

Size	19" (SXGA)
Resolution	1280 × 1024
Touch Type	Resistive (RTP)
Touch Interface	USB (I2C / RS232 opt.)
Display Interface	LVDS
Brightness	350 ~ 1500 cd/m ² (options)
Active Area	376.3 × 301.1 mm
Module Outline	396 × 324 mm
DCL Part Number	312364-01

APPLICATIONS Industrial HMI · Medical devices · EV charging · Kiosks

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com