OPEN FRAME MONITOR

# 10.1" WXGA Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 450 nit 1280 × 800 panel, VGA / HDMI inputs.

DCL P/N **400277-01** TAA COMPLIANT



| 10.1" | 450 | 1280×800 | -20~55°C |
|---|---|---|---|
| DIAGONAL | NITS | WXGA | OPERATING |

## KEY FEATURES

- 450 nit panel
- 1280 × 800 WXGA, 176° / 176° viewing
- VGA and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

## SPECIFICATIONS

| | |
|---|---|
| Size | **10.1" (WXGA)** |
| Resolution | **1280 × 800** |
| Brightness | **450 cd/m²** |
| Active Area | **217 × 135.6 mm** |
| Viewing Angle (H/V) | **176° / 176°** |
| Touch | **Optional (PCAP / resistive)** |
| Video Inputs | **VGA / HDMI** |
| Control | **RS-232 OSD** |
| Mounting | **Ear bracket / VESA** |
| Power | **12 V DC** |
| Operating Temp. | **-20 ~ +55 °C** |
| DCL Part Number | **400277-01** |

**APPLICATIONS** Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dcltek.com · 1-800-407-8917
www.dcltek.com



Specifications subject to change without notice. Image is representative of the product family.