

OPEN FRAME MONITOR

15.6" FHD Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 450 nit 1920 × 1080 panel, VGA / DVI / HDMI inputs.

DCL P/N

400290-01



TAA COMPLIANT



15.6"

DIAGONAL

450

NITS

1920×1080

FHD

-20~55°C

OPERATING

KEY FEATURES

- 450 nit panel
- 1920 × 1080 FHD, 170° / 170° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	15.6" (FHD)
Resolution	1920 × 1080
Brightness	450 cd/m ²
Active Area	344.2 × 193.6 mm
Viewing Angle (H/V)	170° / 170°
Touch	Optional (PCAP / resistive)
Video Inputs	VGA / DVI / HDMI
Control	RS-232 OSD
Mounting	Ear bracket / VESA
Power	12 V DC
Operating Temp.	-20 ~ +55 °C
DCL Part Number	400290-01

APPLICATIONS Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com