

OPEN FRAME TOUCH MONITOR

10.4" SVGA Open Frame Touch Monitor

Ready-to-integrate touch monitor for kiosks, HMI and semi-outdoor enclosures — 250 nit 800 × 600 panel, VGA / HDMI inputs.

DCL P/N

400320-01



TAA COMPLIANT



10.4"

DIAGONAL

250

NITS

800×600

SVGA

-10~50°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 250 nit panel
- 800 × 600 SVGA, 160° / 130° viewing
- VGA and HDMI video inputs
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Multi-touch with USB touch interface
- Options: AG / AR / AF / UV-cut glass, 2–6 mm impact glass, water-tolerant touch

SPECIFICATIONS

Size	10.4" (SVGA)
Resolution	800 × 600
Brightness	250 cd/m ²
Active Area	211.2 × 158.4 mm
Viewing Angle (H/V)	160° / 130°
Touch	PCAP, USB
Video Inputs	VGA / HDMI
Mounting	Ear bracket / VESA
Power	12 V DC
Operating Temp.	-10 ~ +50 °C
DCL Part Number	400320-01

APPLICATIONS Kiosks · Industrial HMI · Medical carts · Marine · EV charging · Food service

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com