

OPEN FRAME TOUCH MONITOR

15" XGA Open Frame Touch Monitor

Ready-to-integrate touch monitor for kiosks, HMI and semi-outdoor enclosures — 300 nit 1024 × 768 panel, VGA / DVI / HDMI inputs.

DCL P/N

400329-01



TAA COMPLIANT



15"

DIAGONAL

300

NITS

1024×768

XGA

-10~50°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 300 nit panel
- 1024 × 768 XGA, 176° / 176° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Multi-touch with USB touch interface
- Options: AG / AR / AF / UV-cut glass, 2–6 mm impact glass, water-tolerant touch

SPECIFICATIONS

Size	15" (XGA)
Resolution	1024 × 768
Brightness	300 cd/m ²
Active Area	304.1 × 228.1 mm
Viewing Angle (H/V)	176° / 176°
Touch	PCAP, USB
Video Inputs	VGA / DVI / HDMI
Control	RS-232 OSD
Mounting	Ear bracket / VESA
Power	12 V DC
Operating Temp.	-10 ~ +50 °C
DCL Part Number	400329-01

APPLICATIONS Kiosks · Industrial HMI · Medical carts · Marine · EV charging · Food service

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917

www.dcltek.com