

OPEN FRAME TOUCH MONITOR

# 17" SXGA Open Frame Touch Monitor

Ready-to-integrate touch monitor for kiosks, HMI and semi-outdoor enclosures — 250 nit 1280 × 1024 panel, VGA / DVI / HDMI inputs.

DCL P/N

**400333-01**



TAA COMPLIANT



**17"**

DIAGONAL

**250**

NITS

**1280×1024**

SXGA

**-10~50°C**

OPERATING

## KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 250 nit panel
- 1280 × 1024 SXGA, 170° / 160° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Multi-touch with USB touch interface
- Options: AG / AR / AF / UV-cut glass, 2–6 mm impact glass, water-tolerant touch

## SPECIFICATIONS

|                     |                       |
|---------------------|-----------------------|
| Size                | 17" (SXGA)            |
| Resolution          | 1280 × 1024           |
| Brightness          | 250 cd/m <sup>2</sup> |
| Active Area         | 337.9 × 270.3 mm      |
| Viewing Angle (H/V) | 170° / 160°           |
| Touch               | PCAP, USB             |
| Video Inputs        | VGA / DVI / HDMI      |
| Control             | RS-232 OSD            |
| Mounting            | Ear bracket / VESA    |
| Power               | 12 V DC               |
| Operating Temp.     | -10 ~ +50 °C          |
| DCL Part Number     | 400333-01             |

**APPLICATIONS** Kiosks · Industrial HMI · Medical carts · Marine · EV charging · Food service

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dcltek.com · 1-800-407-8917

www.dcltek.com