CLOSED FRAME MONITOR

32" FHD Closed Frame Monitor

Fully enclosed stand-alone industrial monitor — 700 nit 1920 × 1080 panel, VGA / DVI / HDMI inputs.

DCL P/N 400394-01 TAA COMPLIANT

32"	700	1920×1080	-10~50°C
DIAGONAL	NITS	FHD	OPERATING

KEY FEATURES

- 700 nit panel
- 1920 × 1080 FHD, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- VESA mounting
- Universal 100–240 V AC internal power supply
- Enclosed metal housing — deploy without a custom enclosure
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	**32" (FHD)**
Resolution	**1920 × 1080**
Brightness	**700 cd/m²**
Active Area	**698.4 × 392.9 mm**
Viewing Angle (H/V)	**178° / 178°**
Touch	**Optional (PCAP / resistive)**
Video Inputs	**VGA / DVI / HDMI**
Control	**RS-232 OSD**
Mounting	**VESA**
Power	**100–240 V AC**
Operating Temp.	**-10 ~ +50 °C**
DCL Part Number	**400394-01**

APPLICATIONS Control rooms · Industrial HMI · Digital signage · Transportation · Retail

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.