

PANEL MOUNT TOUCH MONITOR

10.4" SVGA Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 300 nit 800 × 600 panel, VGA / HDMI inputs.

DCL P/N

400438-01



TAA COMPLIANT



10.4"

DIAGONAL

300

NITS

800×600

SVGA

-10~50°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 300 nit panel
- 800 × 600 SVGA, 160° / 130° viewing
- VGA and HDMI video inputs
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

SPECIFICATIONS

Size	10.4" (SVGA)
Resolution	800 × 600
Brightness	300 cd/m ²
Active Area	211.2 × 158.4 mm
Viewing Angle (H/V)	160° / 130°
Touch	PCAP, USB
Video Inputs	VGA / HDMI
Mounting	Panel mount
Front Sealing	IP65
Power	12 V DC
Operating Temp.	-10 ~ +50 °C
DCL Part Number	400438-01

APPLICATIONS Industrial HMI · Food processing · Marine · EV charging · Machine control

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com