

PANEL MOUNT TOUCH MONITOR

17" SXGA Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 350 nit 1280 × 1024 panel, VGA / DVI / HDMI inputs.

DCL P/N

400452-01



TAA COMPLIANT



17"

DIAGONAL

350

NITS

1280×1024

SXGA

-20~55°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 350 nit panel
- 1280 × 1024 SXGA, 160° / 140° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

SPECIFICATIONS

Size	17" (SXGA)
Resolution	1280 × 1024
Brightness	350 cd/m ²
Active Area	337.9 × 270.3 mm
Viewing Angle (H/V)	160° / 140°
Touch	PCAP, USB
Video Inputs	VGA / DVI / HDMI
Control	RS-232 OSD
Mounting	Panel mount
Front Sealing	IP65
Power	12 V DC
Operating Temp.	-20 ~ +55 °C
DCL Part Number	400452-01

APPLICATIONS Industrial HMI · Food processing · Marine · EV charging · Machine control

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com