

PANEL MOUNT TOUCH MONITOR

# 19" SXGA Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 500 nit 1280 × 1024 panel, VGA / DVI / HDMI inputs.

DCL P/N

**400455-01**



TAA COMPLIANT



**19"**

DIAGONAL

**500**

NITS

**1280×1024**

SXGA

**-10~50°C**

OPERATING

## KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 500 nit panel
- 1280 × 1024 SXGA, 170° / 160° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

## SPECIFICATIONS

|                     |                       |
|---------------------|-----------------------|
| Size                | 19" (SXGA)            |
| Resolution          | 1280 × 1024           |
| Brightness          | 500 cd/m <sup>2</sup> |
| Active Area         | 376.3 × 301.1 mm      |
| Viewing Angle (H/V) | 170° / 160°           |
| Touch               | PCAP, USB             |
| Video Inputs        | VGA / DVI / HDMI      |
| Control             | RS-232 OSD            |
| Mounting            | Panel mount           |
| Front Sealing       | IP65                  |
| Power               | 12 V DC               |
| Operating Temp.     | -10 ~ +50 °C          |
| DCL Part Number     | 400455-01             |

**APPLICATIONS** Industrial HMI · Food processing · Marine · EV charging · Machine control

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com