

OPEN FRAME MONITOR

# 10.1" WXGA High-Bright Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 1200 nit 1280 × 800 panel, VGA / HDMI inputs.

DCL P/N

**4A00258-01**



TAA COMPLIANT



**10.1"**

DIAGONAL

**1200**

NITS

**1280×800**

WXGA

**-10~50°C**

OPERATING

## KEY FEATURES

- 1200 nit high-brightness panel with auto-brightness control
- 1280 × 800 WXGA, 170° / 170° viewing
- VGA and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

## SPECIFICATIONS

|                     |                                       |
|---------------------|---------------------------------------|
| Size                | 10.1" (WXGA)                          |
| Resolution          | 1280 × 800                            |
| Brightness          | 1200 cd/m <sup>2</sup> (auto-dimming) |
| Active Area         | 217 × 135.6 mm                        |
| Viewing Angle (H/V) | 170° / 170°                           |
| Touch               | Optional (PCAP / resistive)           |
| Video Inputs        | VGA / HDMI                            |
| Control             | RS-232 OSD                            |
| Mounting            | Ear bracket / VESA                    |
| Power               | 12 V DC                               |
| Operating Temp.     | -10 ~ +50 °C                          |
| DCL Part Number     | 4A00258-01                            |

**APPLICATIONS** Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dccltek.com · 1-800-407-8917

www.dcltek.com