

OPEN FRAME MONITOR

10.4" SVGA High-Bright Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 1200 nit 800 × 600 panel, VGA / HDMI inputs.

DCL P/N

4A00262-01



TAA COMPLIANT



10.4"

DIAGONAL

1200

NITS

800×600

SVGA

-20~55°C

OPERATING

KEY FEATURES

- 1200 nit high-brightness panel with auto-brightness control
- 800 × 600 SVGA, 160° / 140° viewing
- VGA and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	10.4" (SVGA)
Resolution	800 × 600
Brightness	1200 cd/m ² (auto-dimming)
Active Area	211.2 × 158.4 mm
Viewing Angle (H/V)	160° / 140°
Touch	Optional (PCAP / resistive)
Video Inputs	VGA / HDMI
Control	RS-232 OSD
Mounting	Ear bracket / VESA
Power	12 V DC
Operating Temp.	-20 ~ +55 °C
DCL Part Number	4A00262-01

APPLICATIONS Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com