OPEN FRAME MONITOR

19" SXGA High-Bright Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 1500 nit 1280 × 1024 panel, VGA / DVI / HDMI inputs.

DCL P/N 4A00297-01 TAA COMPLIANT

19"	1500	1280×1024	-20~55°C
DIAGONAL	NITS	SXGA	OPERATING

KEY FEATURES

- 1500 nit high-brightness panel with auto-brightness control
- 1280 × 1024 SXGA, 170° / 160° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	**19" (SXGA)**
Resolution	**1280 × 1024**
Brightness	**1500 cd/m² (auto-dimming)**
Active Area	**376.3 × 301.1 mm**
Viewing Angle (H/V)	**170° / 160°**
Touch	**Optional (PCAP / resistive)**
Video Inputs	**VGA / DVI / HDMI**
Control	**RS-232 OSD**
Mounting	**Ear bracket / VESA**
Power	**12 V DC**
Operating Temp.	**-20 ~ +55 °C**
DCL Part Number	**4A00297-01**

APPLICATIONS Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.