OPEN FRAME MONITOR

# 43" FHD High-Bright Open Frame Monitor

Industrial open frame monitor built to mount behind your bezel — 1500 nit 1920 × 1080 panel, VGA / DVI / HDMI inputs.

DCL P/N **4A00322-01**

TAA COMPLIANT

| 43" | 1500 | 1920×1080 | -10~55°C |
|---|---|---|---|
| DIAGONAL | NITS | FHD | OPERATING |

## KEY FEATURES

- 1500 nit high-brightness panel with auto-brightness control
- 1920 × 1080 FHD, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Flexible ear-bracket or VESA mounting
- Universal 100–240 V AC internal power supply
- Steel open-frame chassis for kiosk and machine integration
- PCAP or resistive touch available as an option

## SPECIFICATIONS

| | |
|---|---|
| Size | **43" (FHD)** |
| Resolution | **1920 × 1080** |
| Brightness | **1500 cd/m² (auto-dimming)** |
| Active Area | **940.9 × 529.3 mm** |
| Viewing Angle (H/V) | **178° / 178°** |
| Touch | **Optional (PCAP / resistive)** |
| Video Inputs | **VGA / DVI / HDMI** |
| Control | **RS-232 OSD** |
| Mounting | **Ear bracket / VESA** |
| Power | **100–240 V AC** |
| Operating Temp. | **-10 ~ +55 °C** |
| DCL Part Number | **4A00322-01** |

**APPLICATIONS** Kiosks · Industrial HMI · Gaming · Medical carts · Digital signage

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dcltek.com · 1-800-407-8917
www.dcltek.com



Specifications subject to change without notice. Image is representative of the product family.