OPEN FRAME TOUCH MONITOR

10.4" XGA High-Bright Open Frame Resistive Touch Monitor

Ready-to-integrate touch monitor for kiosks, HMI and semi-outdoor enclosures — 2000 nit 1024 × 768 panel, VGA / HDMI inputs.

DCL P/N 4A00347-01

TAA COMPLIANT



10.4"	2000	1024×768	-20~55°C
DIAGONAL	NITS	XGA	OPERATING

KEY FEATURES

- Resistive touch — glove and stylus friendly, USB interface
- 2000 nit high-brightness panel with auto-brightness control
- 1024 × 768 XGA, 176° / 176° viewing
- VGA and HDMI video inputs
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Options: AG / AR / AF / UV-cut glass, 2–6 mm impact glass

SPECIFICATIONS

Size	**10.4" (XGA)**
Resolution	**1024 × 768**
Brightness	**2000 cd/m² (auto-dimming)**
Active Area	**210.4 × 157.8 mm**
Viewing Angle (H/V)	**176° / 176°**
Touch	**Resistive, USB**
Video Inputs	**VGA / HDMI**
Mounting	**Ear bracket / VESA**
Power	**12 V DC**
Operating Temp.	**-20 ~ +55 °C**
DCL Part Number	**4A00347-01**

APPLICATIONS Kiosks · Industrial HMI · Medical carts · Marine · EV charging · Food service

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.