

OPEN FRAME TOUCH MONITOR

10.4" XGA High-Bright Open Frame Touch Monitor

Ready-to-integrate touch monitor for kiosks, HMI and semi-outdoor enclosures — 1000 nit 1024 × 768 panel, VGA / HDMI inputs.

DCL P/N

4A00348-01



TAA COMPLIANT



10.4"

DIAGONAL

1000

NITS

1024×768

XGA

-20~55°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 1000 nit high-brightness panel with auto-brightness control
- 1024 × 768 XGA, 176° / 176° viewing
- VGA and HDMI video inputs
- Flexible ear-bracket or VESA mounting
- Single 12 V DC supply
- Multi-touch with USB touch interface
- Options: AG / AR / AF / UV-cut glass, 2–6 mm impact glass, water-tolerant touch

SPECIFICATIONS

Size	10.4" (XGA)
Resolution	1024 × 768
Brightness	1000 cd/m ² (auto-dimming)
Active Area	210.4 × 157.8 mm
Viewing Angle (H/V)	176° / 176°
Touch	PCAP, USB
Video Inputs	VGA / HDMI
Mounting	Ear bracket / VESA
Power	12 V DC
Operating Temp.	-20 ~ +55 °C
DCL Part Number	4A00348-01

APPLICATIONS Kiosks · Industrial HMI · Medical carts · Marine · EV charging · Food service

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com