

CLOSED FRAME MONITOR

10.1" WXGA High-Bright Closed Frame Monitor

Fully enclosed stand-alone industrial monitor — 1200 nit
1280 × 800 panel, VGA / HDMI inputs.

DCL P/N

4A00416-01



TAA COMPLIANT



10.1"

DIAGONAL

1200

NITS

1280×800

WXGA

-10~50°C

OPERATING

KEY FEATURES

- 1200 nit high-brightness panel with auto-brightness control
- 1280 × 800 WXGA, 170° / 170° viewing
- VGA and HDMI video inputs
- RS-232 OSD control for remote setup
- VESA mounting
- Single 12 V DC supply
- Enclosed metal housing — deploy without a custom enclosure
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	10.1" (WXGA)
Resolution	1280 × 800
Brightness	1200 cd/m ² (auto-dimming)
Active Area	217 × 135.6 mm
Viewing Angle (H/V)	170° / 170°
Touch	Optional (PCAP / resistive)
Video Inputs	VGA / HDMI
Control	RS-232 OSD
Mounting	VESA
Power	12 V DC
Operating Temp.	-10 ~ +50 °C
DCL Part Number	4A00416-01

APPLICATIONS Control rooms · Industrial HMI · Digital signage · Transportation · Retail

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com