CLOSED FRAME MONITOR

# 12.1" WXGA High-Bright Closed Frame Monitor

Fully enclosed stand-alone industrial monitor — 1800 nit 1280 × 800 panel, VGA / DVI / HDMI inputs.

**DCL P/N** 4A00431-01 TAA COMPLIANT

| 12.1" | 1800 | 1280×800 | -20~55°C |
|---|---|---|---|
| DIAGONAL | NITS | WXGA | OPERATING |

## KEY FEATURES

- 1800 nit high-brightness panel with auto-brightness control
- 1280 × 800 WXGA, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- VESA mounting
- Single 12 V DC supply
- Enclosed metal housing — deploy without a custom enclosure
- PCAP or resistive touch available as an option

## SPECIFICATIONS

| | |
|---|---|
| Size | **12.1" (WXGA)** |
| Resolution | **1280 × 800** |
| Brightness | **1800 cd/m² (auto-dimming)** |
| Active Area | **261.1 × 163.2 mm** |
| Viewing Angle (H/V) | **178° / 178°** |
| Touch | **Optional (PCAP / resistive)** |
| Video Inputs | **VGA / DVI / HDMI** |
| Control | **RS-232 OSD** |
| Mounting | **VESA** |
| Power | **12 V DC** |
| Operating Temp. | **-20 ~ +55 °C** |
| DCL Part Number | **4A00431-01** |

**APPLICATIONS** Control rooms · Industrial HMI · Digital signage · Transportation · Retail

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dcltek.com · 1-800-407-8917
www.dcltek.com



Specifications subject to change without notice. Image is representative of the product family.