CLOSED FRAME MONITOR

17" SXGA High-Bright Closed Frame Monitor

Fully enclosed stand-alone industrial monitor — 1500 nit 1280 × 1024 panel, VGA / DVI / HDMI inputs.

DCL P/N 4A00446-01 TAA COMPLIANT

17"	1500	1280×1024	-20~55°C
DIAGONAL	NITS	SXGA	OPERATING

KEY FEATURES

- 1500 nit high-brightness panel with auto-brightness control
- 1280 × 1024 SXGA, 160° / 140° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- VESA mounting
- Single 12 V DC supply
- Enclosed metal housing — deploy without a custom enclosure
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	**17" (SXGA)**
Resolution	**1280 × 1024**
Brightness	**1500 cd/m² (auto-dimming)**
Active Area	**337.9 × 270.3 mm**
Viewing Angle (H/V)	**160° / 140°**
Touch	**Optional (PCAP / resistive)**
Video Inputs	**VGA / DVI / HDMI**
Control	**RS-232 OSD**
Mounting	**VESA**
Power	**12 V DC**
Operating Temp.	**-20 ~ +55 °C**
DCL Part Number	**4A00446-01**

APPLICATIONS Control rooms · Industrial HMI · Digital signage · Transportation · Retail

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.