

CLOSED FRAME MONITOR

18.5" WXGA High-Bright Closed Frame Monitor

Fully enclosed stand-alone industrial monitor — 1000 nit
1366 × 768 panel, VGA / DVI / HDMI inputs.

DCL P/N

4A00456-01



TAA COMPLIANT



18.5"

DIAGONAL

1000

NITS

1366×768

WXGA

-10~50°C

OPERATING

KEY FEATURES

- 1000 nit high-brightness panel with auto-brightness control
- 1366 × 768 WXGA, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- VESA mounting
- Single 12 V DC supply
- Enclosed metal housing — deploy without a custom enclosure
- PCAP or resistive touch available as an option

SPECIFICATIONS

Size	18.5" (WXGA)
Resolution	1366 × 768
Brightness	1000 cd/m ² (auto-dimming)
Active Area	409.8 × 230.4 mm
Viewing Angle (H/V)	178° / 178°
Touch	Optional (PCAP / resistive)
Video Inputs	VGA / DVI / HDMI
Control	RS-232 OSD
Mounting	VESA
Power	12 V DC
Operating Temp.	-10 ~ +50 °C
DCL Part Number	4A00456-01

APPLICATIONS Control rooms · Industrial HMI · Digital signage · Transportation · Retail

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com