PANEL MOUNT TOUCH MONITOR

10.1" WXGA High-Bright Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 1200 nit 1280 × 800 panel, VGA / HDMI inputs.

DCL P/N 4A00558-01 · TAA COMPLIANT



10.1"	1200	1280×800	-10~50°C
DIAGONAL	NITS	WXGA	OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 1200 nit high-brightness panel with auto-brightness control
- 1280 × 800 WXGA, 170° / 170° viewing
- VGA and HDMI video inputs
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

SPECIFICATIONS

Size	**10.1" (WXGA)**
Resolution	**1280 × 800**
Brightness	**1200 cd/m² (auto-dimming)**
Active Area	**217 × 135.6 mm**
Viewing Angle (H/V)	**170° / 170°**
Touch	**PCAP, USB**
Video Inputs	**VGA / HDMI**
Mounting	**Panel mount**
Front Sealing	**IP65**
Power	**12 V DC**
Operating Temp.	**-10 ~ +50 °C**
DCL Part Number	**4A00558-01**

APPLICATIONS Industrial HMI · Food processing · Marine · EV charging · Machine control

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcltek.com · 1-800-407-8917
www.dcltek.com

Specifications subject to change without notice. Image is representative of the product family.