

PANEL MOUNT TOUCH MONITOR

12.1" SVGA High-Bright Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 1500 nit 800 × 600 panel, VGA / DVI / HDMI inputs.

DCL P/N

4A00567-01



TAA COMPLIANT



12.1"

DIAGONAL

1500

NITS

800×600

SVGA

-20~55°C

OPERATING

KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 1500 nit high-brightness panel with auto-brightness control
- 800 × 600 SVGA, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

SPECIFICATIONS

Size	12.1" (SVGA)
Resolution	800 × 600
Brightness	1500 cd/m ² (auto-dimming)
Active Area	246 × 184.5 mm
Viewing Angle (H/V)	178° / 178°
Touch	PCAP, USB
Video Inputs	VGA / DVI / HDMI
Control	RS-232 OSD
Mounting	Panel mount
Front Sealing	IP65
Power	12 V DC
Operating Temp.	-20 ~ +55 °C
DCL Part Number	4A00567-01

APPLICATIONS Industrial HMI · Food processing · Marine · EV charging · Machine control

Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

Request a quote or samples

sales@dcletek.com · 1-800-407-8917

www.dcltek.com