PANEL MOUNT TOUCH MONITOR

# 12.1" XGA High-Bright Panel Mount PCAP Touch Monitor

Panel-mount touch monitor with sealed front for washdown and harsh environments — 1000 nit 1024 × 768 panel, VGA / DVI / HDMI inputs.

**DCL P/N** 4A00568-01 · TAA COMPLIANT




| 12.1" | 1000 | 1024×768 | -10~50°C |
|---|---|---|---|
| DIAGONAL | NITS | XGA | OPERATING |

## KEY FEATURES

- Projected capacitive multi-touch, USB touch interface
- 1000 nit high-brightness panel with auto-brightness control
- 1024 × 768 XGA, 178° / 178° viewing
- VGA, DVI and HDMI video inputs
- RS-232 OSD control for remote setup
- Single 12 V DC supply
- IP65-rated sealed front panel
- Flush panel-mount design for machine and cabinet integration

## SPECIFICATIONS

| | |
|---|---|
| Size | **12.1" (XGA)** |
| Resolution | **1024 × 768** |
| Brightness | **1000 cd/m² (auto-dimming)** |
| Active Area | **245.8 × 184.3 mm** |
| Viewing Angle (H/V) | **178° / 178°** |
| Touch | **PCAP, USB** |
| Video Inputs | **VGA / DVI / HDMI** |
| Control | **RS-232 OSD** |
| Mounting | **Panel mount** |
| Front Sealing | **IP65** |
| Power | **12 V DC** |
| Operating Temp. | **-10 ~ +50 °C** |
| DCL Part Number | **4A00568-01** |

**APPLICATIONS** Industrial HMI · Food processing · Marine · EV charging · Machine control

## Design it in with DCL.

Samples, custom brightness, cover glass, touch tuning and cable assemblies — backed by US-based engineering and in-country factory oversight. **Manufactured in a TAA-compliant geography.**

**Request a quote or samples**

sales@dcltek.com · 1-800-407-8917
www.dcltek.com



Specifications subject to change without notice. Image is representative of the product family.