Request information

27 Inch

Curved Touchmonitor

The novelty of curved touchmonitors brings an air of mystique to the display market. When LED-Framed lights are added, it easily becomes the prima donna of touch displays. General Touch mass produces these curved beauties in-house and they come in C, J or S curve-types with the classic curvature radius of R1500 in sizes ranging from 23.6 to 55 inches. To date, the 55 inch J-type has attained a breakthrough curvature radius of R800.

The large-sized 43-55 inch portrait curved touch screen provides an immersive and expansive user experience from top to bottom in diverse gaming and interactive scenarios. The medium-sized 23.6-32 inch landscape curved touch screen design is based on user-centered ergonomics, reducing fatigue in the human-computer interaction process, allowing users to play longer, fuller and happier.

General Touch offers both the Open Frame and Closed Frame curved displays. For a flushing appearance when integrated into a cabinet, the Open Frame is the straightforward choice. The Closed Frame allows the display to float on the surface of the cabinet though VESA and hinge mounting options, adding a tinge look of sophistication. When combined with Halo/Edge/Front LED-Framed lights, the curved display looks like it is dancing rhythmically. If a Closed Frame is in floating mount, adding rear LED lights would produce a silhouette effect.

- Gaming
- Kiosk
- Vending Machine

Features & Benefits

- Curved shape, C design, unique and interactive motivation
- 3 sides LED framed, No hot spot, no dark spot, no dark corner, high level uniformity
- Landscape curved, open frame, compatible with various application

SPECIFICATIONS

Product Name	27 Inch Curved Touchmonitor
Model	OTC277
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	596.74mm × 335.66mm
Native Resolution	1920 × 1080 @ 60Hz
Response Time (Typ.)	15ms
Display Colors	16.7M
Luminance (Typ.)	500nits
Contrast Ratio (Typ.)	3000:1
Viewing Angle (Typ.)	Horizontal: CR≥10 89°/89° Vertical: CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	PCAP
Cover Glass Treatment	Strengthened
Impact Resistance Level	IK07
Thickness (Total)	4.5mm
Light Transmission	≥ 83%
Response Time (Typ.)	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 100mm × 100mm, 75mm × 75mm Side mounting, see drawing for details
Outline Dimensions (W×H×D)	677.2mm × 408.1mm × 70.9mm, curvature radius 1494mm
Power Supply	Input Voltage Range: Monitor: +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter RGB LED Lights: +12VDC ± 5%, mating Molex 43025-0600 Optional LED controller (External): +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	36W (Monitor without RGB LED Lights) 15W (RGB LED Lights)
Operating Altitude	≤ 3000m
Temperature Range	Operating: 0℃ to 40℃, storage: -20℃ to 60℃
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, DP, USB (Type B)
Accessories	Optional

Proudly supported by DCLTEK in the USA WWW.DCLTEK.COM 1-800-407-8917 SALES@DCLTEK.COM

Carton Box Dimensions	810mm (L) × 205mm (W) × 555mm (H), 1 unit in one carton
Weight	Net: 9.5kg, Gross: 11.5kg
MTBF	50,000 hours demonstrated
LED Lights Color	Multicolor
LED Lights Location	3 LED lights bar (Front, Edge)
LED Controller (External)	Optional
Agency Approvals	CE, FCC, UKCA
Warranty	1 year

Ordering Information

Model	Part Number	Description
OTC277-RC5000-UD3230-1.1	10202020163R	27” “C type”, landscape curved, FHD, 16:9, 500nits, PCAP, USB, HDMI/DP, open frame, 3 LED lights bar (Front, Edge)

Optional Accessories

Model	Part Number	Description
USB Cable	30302050006R	USB Cable A Male-B Male 1500mm
HDMI Cable	30302030001R	HDMI Cable Male-Male 1500 mm
DP Cable	30302010001R	DP Cable Male-Male 1500 mm
Adapter	30207010005R	Power Adapter 12V / 50W / 2.5mm / 1500mm
Power Cable	30301010018R 30301010011R 30301010010R	UK EU 1500mm US
LED Controller Kit	20701040010R	12 V / 50 W Addressable LED Controller Kit

Note: Includes a 1000mm LED strip cable.
If you want to design the LED strip cable according to your application, please adopt the unshielded and non-twisted wires. The length should be no more than 2m, and the wire diameter should be more than 20AWG.
Please feel free to contact us if you need assistance.

Go to *www.generaltouch.com* for more products and information, or contact us.
General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
Fax: 0086-28-85124115
E-mail: info@generaltouch.com
http://*www.generaltouch.com*

Proudly supported by DCLTEK in the USA WWW.DCLTEK.COM 1-800-407-8917 SALES@DCLTEK.COM