Request information

7" Panel Mount

DuraBrite Series
Outdoor High-BrightTouchmonitor

Operating outdoor kiosks is not for the fainthearted. The average touch display just won't do because of the numerous 'moving parts' in an outdoor environment. You would need both brains and brawn for successful deployment. To take on these physical challenges, General Touch has come up with the DuraBrite series outdoor high-brightness touchmonitors. Currently available in sizes from 7 to 32 inches, the state-of-the-art DuraBrite series have been carefully designed and produced with innovative enhancements and capabilities. These enhancements would facilitate optimal performance in adverse environmental conditions, making the series ideal for use in payment terminals, self-service kiosks, EV charging stations, ticketing machines, vending machines, outdoor signage and more.

EV Charging Station

Self-service Kiosk

Vending Machine

Ticketing Machines

Parking Pay Station

Outdoor Signage

Features & Benefits

- High-Tni up to 105° allows a wide operating temperature range from -20°C to 60°C, eradicating any fear of display black-out.
- Brightness up to 1500 nits and anti-glare coating delivers better visuals and readability even in direct sunlight.
- 50K hours LED lifetime - 50,000 hours of MTBF for longlasting 24/7 operation.
- UV&IR protection minimizes internal heat accumulation and decelerates components aging significantly.
- UV-resistant ink prevents the screen printing from peeling effectively.
- The touch performance is heightened to facilitate smooth operations even when there are water droplets on the touch glass.
- Advanced optical bonding takes interior fogging out of the equation.
- Automatic brightness adjustment corresponds with ambient light to ensure 24/7 stable performance and to extend LCD panel lifespan.
- The metal parts have been beefed up with rustproofing for all-year outdoor deployment.
- When the touchmonitor is properly fitted to the kiosk without any gaps, the waterproof and dustproof rating can reach IP65 & Nema 4x , further fortifying the whole touch unit.

SPECIFICATIONS

Name	7 Inch Outdoor Touchmonitor
Model	PSL073
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	15:9
Active Area (W x H)	152.40mm × 91.44mm
Native Resolution	800×480@60Hz
Response Time (Typ.)	25ms
TNI	105℃
Display Colors	16.7M
Luminance (Typ.)	1500nits, with PCAP 1170 nits
Contrast Ratio (Typ.)	1000:1
LED Backlight Time(Min)	100,000 hours
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10 88° /88° Vertical (Up/Down) CR≥10 88° /88°
Touch Screen Parameters	
Touch Technology	PCAP
Cover Glass Treatment	Strengthened
Cover Glass Surface Treatment	Anti-Glare
Impact resistance Level	IK8
Ink	UV-resistant
Active Area(W x H)	152.4mm × 91.4mm±0.3mm
Thickness(Total)	7.5mm±0.3mm
Light Transmission	≥78%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Feature	UV&IR Filter
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 50mm × 50mm, Panel mount
Outline Dimensions（W×H×D）	213.8mm × 156.7mm × 61.1mm
Power Supply	Input Voltage Range: +12VDC ± 5%, Coaxial power jack 2.5mm pin outer diameter

Proudly supported by DCLTEK in the USA WWW.DCLTEK.COM 1-800-407-8917 SALES@DCLTEK.COM

On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	9W
Light Sensor	Yes
IP Level	Front Panel IP65
Bonding Type	Optical bonding
Operating Altitude	≤3000m
Operating Time	7*24hrs with dynamic video
Temperature Range	Operating: -20℃ to 60℃, Storage: -20℃ to 70℃
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B, For Touch)
Accessories	Cables: VGA×1, USB×1, 1.5m Length, Clamps × 8
Carton Box Dimensions	375mm (L) × 345mm (W) × 165mm (H)
Weight	Net: 1.47kg, Gross: 2.2kg
Agency Approvals	CE, FCC, UKCA
MTBF	50,000 hours demonstrated
Warranty	1 year

Notes：The light leakage (mura) standard of the edge area surrounding active area is invisible under 1% ND filter.

Ordering Information		
Model	Part Number	Description
PSL073-RC80A0-UHBAL0-1.0	10202010727R	7”, panel mount, 15:9, 1500nits, PCAP, USB, VGA & HDMI, Sunlight readable, Outdoor, Black, IP65 Front

Contact sales for other options

Optional Accessories			
Model	Part Number	Description	
Power Cable	30301010018R	UK	1500mm
	30301010011R	EU	
	30301010010R	US	
HDMI Cable	30302030001R		1500mm
Adapter	30207010005R	12V/4.17A, DC Cable: 1500mm, DC barrel plug 2.5mm pin inner diameter	

Proudly supported by DCLTEK in the USA WWW.DCLTEK.COM 1-800-407-8917 SALES@DCLTEK.COM

Drawing

TITLE: PSL073-RC80A0-UHBAL0-1.0

MARK	AMEND	SIGNATURE
⚠		











A': M4 THREADS, x4, MAX SCREW DEPTH = 6MM



General Touch Co.,Ltd.					
SPECIFICATION	OVERALL DIMENSIONS	213.8x156.7x61.1	ANTI-GLARE	Y ☑ N ☐	
UNIT / DATE	VIEW AREA	152.4x91.4			DESIGNER: Deng Chunhua
MM / 2025/11/11	GLASS THICKNESS	6.0 MM			
PROJECTION:	SILK SCREEN COLOR	BLACK			CHECKED BY: Han Jin
	MOUNTING	VESA ☐	BRACKET ☑		
SHEET 1 of 2	NOTES				APPROVED BY: Zhou Bolin
VER: 1.0 / SCALE: 1:1	TOUCH TECHNOLOGY	P-CAP	√	SAW	
TOLERANCE: ±1.0MM		NON-TOUCH		RESISTIVE	

DO NOT SCALE DRAWING

Go to *www.generaltouch.com* for more products and information, or contact us.
General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
Fax: 0086-28-85124115
E-mail: info@generaltouch.com
http://*www.generaltouch.com*

Proudly supported by DCLTEK in the USA WWW.DCLTEK.COM 1-800-407-8917 SALES@DCLTEK.COM